



**RFS Cable and
Connectors Available
through Cablcon**

When an installation doesn't permit the use of factory tested, single or double ended preformed jumpers, Cablcon has the necessary materials to help you complete your project on time. Cablcon supports the distribution of RFS coaxial cable and connectors for field termination, and offers additional services as part of our Rack & Stack and Kitting programs. For more information on these programs, please contact your Cablcon Account Manager.

CABLE	
RFS PN	Description
HCA78-50JPL	7/8" Air Dielectric Plenum-Rated Corrugated Copper
ICA12-50JPL	1/2" Copper plenum-rated air dielectric cable, blue
ICA12-50JPLW	1/2" Copper plenum-rated air dielectric cable, white
LCF12-50J	1/2" Coaxial Cable, Std. Corrugated Copper
LCF12-50JFN	1/2" Coaxial Cable, Std. Corrugated Copper, Fire-Rated
LCF158-50JA-A0	1-5/8" Coaxial Cable, Std. Corrugated Copper
LCF38-50J	3/8" Coaxial Cable, Std. Corrugated Copper
LCF78-50JA	7/8" Coaxial Cable, Std. Corrugated Copper
LCF78-50JFNA	7/8" Coaxial Cable, Std. Corrugated Copper, Fire-Rated
SCF12-50J	1/2" Coaxial Cable, Superflexible. Corrugated Copper
SCF12-50JFN	1/2" Coaxial Cable, Superflexible. Corrugated Copper, Fire-Rated
UCF114-50JA-A0	1-1/4 " Coax Ultraflexible Corrugated Copper

CONNECTORS	
RFS PN	Description
716F-LCF114-D01K	7/16 DIN Female straight connector for 1-1/4" cable
716F-LCF12-D01	7/16 DIN Female for standard 1/2" cable
716F-LCF158-D01K	7/16 DIN Female Conn- Positive- for use with LCF 1-5/8" coax
716F-LCF78-D01K	7/16 DIN Female Conn- Positive- for use with LCF 7/8" coax
716F-SCF12-D01	7/16 DIN Female connector for 1/2" superflex
716M-LCF12-D01	7/16 DIN Male for standard flex 1/2"
716M-LCF158-D01K	7/16 DIN Male Conn- Positive- for use with LCF 1-5/8" coax
716M-LCF78-D01K	7/16 DIN Male Conn- Positive- for use with LCF 7/8" coax
716MR-LCF12-D01	7/16 DIN Male right angle for standard flex 1/2"
716M-SCF12-D01	7/16 DIN Male for superflex 1/2"
NF-LCF114-D01K	N Female connector for 1-1/4" cable
NF-LCF158-D01K	N Female Conn- use with LCF 1-5/8" coax
NF-LCF78-D01K	N Female Conn- Positive- 7/16 use with LCF 7/8" coax
NF-SCF12-D01	N Female connector for superflex 1/2"
NM-LCF12-D01	N Male connector for standard flex 1/2"
NM-LCF158-D01K	N Male Conn- use with LCF 1-5/8" coax
NM-LCF78-D01K	N Male Conn- Positive- 7/16 use with LCF 7/8" coax
NMR-LCF12-D01	N Male right angle connector for 1/2" standard flex
NMR-SCF12-D01	N Male right angle connector for superflex 1/2"
NM-SCF12-D01	N Male connector for superflex 1/2"

DALLAS • DETROIT

Corporate Offices: 359 Robbins Drive • Troy, MI 48083-4561

Phone: 888.8.CABLCON • Fax: 248.588.1462 • www.cablcon.com



TL9000

