



Wall Mount Patch Panel
Ordering Information
(fiber pigtail applications)

- Steel housing with black powder coat finish
- Enclosure thickness: 16 Gauge



2 Plate Configuration



4 Plate Configuration

Fiber Capacity	Dimensions
1 adapter plate, 6-12 capacity	7"W x 1.5"D x 6.5"H
2 adapter plates, 12-24 capacity	15.625"W x 2.125"D x 13"H
4 adapter plates, 24-48 capacity	15.625"W x 3.5"D x 15"H
8 adapter plates, 48-96 capacity	12.25"W x 6"D x 17"H

343 [] [] **W** **P** [] [] - [] [] [] [] [] [] [] []

Loaded Ports
 0 = 0
 12 = 1
 24 = 2
 36 = 3
 48 = 4
 72 = 6
 96 = 7

Panel Size
 1 Plate
 2 Plates
 4 Plates
 8 Plates

Wall Mount
Patch

Cable Exit
 Top Left A
 Top Right B
 Top Left & Top Right (2 trunks) C
 Bottom Left D
 Bottom Right E
 Bottom Left & Right (2 trunks) F
 No Pigtail 0

Cable Length
 Specify in feet if pigtail is used.
 If not, populate with 000.
 ex. (005 = 5 Feet), (000 = No Pigtail)

Connector/Adapter Style

SM SC Simplex UPC Polish	01
SM SC Duplex UPC Polish	02
SM FC Simplex D-Hole UPC Polish	04
SM FC Simplex D-Hole APC Polish	05
SM ST Metal Simplex UPC Polish	13
MM SC Simplex PC Polish	07
MM SC Duplex PC Polish	08
MM FC Simplex D-Hole PC Polish	10
SM SC Simplex APC Polish	11
SM SC Duplex APC Polish	12
SM ST 12-Port (High Density) UPC Polish	06
SM LC Duplex UPC Polish	15
SM LC Duplex APC Polish	17
SM LC Quad (High Density) UPC Polish	29
SM MPO Rear/LC Front UPC Polish	18
SM MPO Rear/LC Front APC Polish	19
SM MPO Rear/SC Front UPC Polish	20
SM MPO Rear/SC Front APC Polish	21
MM 62.5 MPO Rear/LC Front PC Polish	22
MM 62.5 MPO Rear/SC Front PC Polish	23
MM 62.5 MPO Rear/ST Front PC Polish	24
MM 50 micron MPO Rear/LC Front PC Polish	25
MM 50 micron MPO Rear/SC Front PC Polish	26
MM 50 micron MPO Rear/ST Front PC Polish	27

Pigtails

No Pigtail	0
SM UPC Polish	2
SM APC Polish	3
MM 50/125 Fiber	4
MM 62.5/125 Fiber	5
MM 100/140 Fiber	6

Cable Type

No Pigtail	00
1.6mm Jacketed Pigtail	01
2.0mm Jacketed Pigtail	02
3.0mm Jacketed Pigtail	03
12 Fiber S/M Indoor Ribbon	07
12 Fiber OFNR	12
12 Fiber Indoor/Outdoor	14
24 Fiber OFNR	24
24 Fiber Indoor/Outdoor	26
48 Fiber OFNR	48
48 Fiber Indoor/Outdoor	50
72 Fiber OFNR	72
72 Fiber Indoor/Outdoor	74
96 Fiber OFNR	96
96 Fiber Indoor/Outdoor	98
144 Fiber Indoor/Outdoor	44
144 Fiber OSP Loose Tube	46

Simplex Ports = 6 Connectors Per Plate
 Duplex Ports = 12 Connectors Per Plate
 Quad Ports = 24 Connectors Per Plate

DALLAS • DETROIT

Corporate Offices: 359 Robbins Drive • Troy, MI 48083
 Phone: 888.8.CABLCON • Fax: 248.588.1462 • www.cablcon.com

